



Fireplace cassettes and doors




I have always been fascinated by the warmth, comfort and feeling of security provided by a crackling open fire. I am passionate about providing outstanding fireplace technology with the very highest level of technical quality and sophisticated innovations. And because we know that the glowing flames of a fireplace are the emotional centre point of your home, we place great value on exquisite design to ensure an exceptional and individual fireplace architecture.

At Spartherm we are driven by our burning ambition to combine the fascination of fire with the demands of the latest lifestyle and living environment. For more than 30 years.

Please accept our warmest welcome

Gerhard Manfred Rokossa

Founder and managing partner







6

7

The benefits of a fireplace cassette:

individually tailored to your requirements?

• better heating capacity

cassette or fireplace door.

- no flying sparks
- controlled combustion
- fuel material is saved
- can be retro-fitted to almost any type of open fireplace

The perfect addition

What appeared to be adventurous to us as a child is an annoyance as an adult: ineffective combustion, ash residues that are difficult to deal with and unpredictable flying sparks at a moderate level of heating capacity are no longer acceptable.

Do you want a fireplace with a modern design, warmth that can be felt rapidly and optimal combustion performance that has been

On the next few pages, you will see that we can provide you with the right solution for your open fireplace in any room situation and any ambience with a Spartherm fireplace

to every fireplace

• no chiseling or masonry work required during installation








Your choice – our range

Available frame finishes


LINEAR Fireplace cassettes



Standard | black



Custom-made model



Standard | black



Stainless steel brushed VAG









"I love my new, old fireplace and enjoy the flickering and warming fire."


Open to modern safety concepts

Enjoy a fire in a contemporary framework. For more safety and healthy, clean air inside and outside.

All Spartherm products fulfil the 2nd level of the German Federal Emission Control Act (BimSchV) and are available in five sizes and in the Standard frame colour, black.

10 11

LINEAR XL 900	11
LINEAR XS 500	12-13
LINEAR S 600	14-15
LINEAR L 800	16-17









LINEAR XS 500

A fascinating interplay of elements. Compact pre-fabricated elements can be integrated expertly into every space and every ambience.



TECHNICAL DATA

Nominal heat output: 4.0 kW · Door function: hinged

Energy efficiency class: A+ · See pages 48-49 for technical details

Installation dimension:















"A cosy place to read her favourite book."

The right setting for more safety

With a fireplace cassette that has been tailor-made just for you, you will increase your feeling of well-being at your usual fireplace with the greatest precision and comfort. Without any time-consuming modifications or a dirty mess.


You can get custom-made special productions for your home from Spartherm.

Custom-made fireplace cassettes are divided into two categories: small up to 700 mm and large from 700 mm, so that we are always able to manufacture the right version for you.

And this comes with the full level of safety and comfort of the Standard fireplace cassette.

20 21

Fireplace cassette 2L / 2R 21
Fireplace cassette 1V 22-23















"I dou't just have my suits tailor-made."

Your style - your wishes

You already have a clear idea of the overall effect your premises should create.

 $We \ manufacture \ fireplace \ cassettes \ according \ to \ your \ wishes \ and \ appropriate \ to \ your \ residential \ design.$

Discover the enormous range of design options that can be achieved using our Spartherm fireplace cassettes.

- Nearly all shapes and sizes can be achieved
- Produced according to your individual specifications
- Many colours and surfaces available for selection
- Professional support and advice
- and much more

Put the finishing touch on your residential ambience and be inspired by our examples.

26

27

3-sided special production	27
Circular special production	28-29
Large special production	30-31







Frames that are out of the ordinary are our speciality. There are almost no limits to the diversity of designs here - and that impresses our customers around the world. TECHNICAL DATA Door function: hinged











"We enjoy the time we spend together in front of the fireplace."


Do away with risks to safety

Don't play with fire! It is therefore an important decision to modernise old and inefficient fireplaces. For more heating capacity, more effective combustion and better air.

Spartherm fireplace cassettes are thus a clean solution for any room situation.

34

35



Fireplace doors

35-39







What a fit!


There are five basic versions of Spartherm fireplace doors, straight, prismatic, 2-sided and 3-sided.

The benefits for you:


- Safe and clean fire
- Draught-free and pleasant heating
- A great deal of radiant heat via the pane
- Custom-made manufacturing in a very wide range of versions

A note:


Fireplace doors change the design of the existing open fireplace. It is therefore necessary to coordinate with your neighbourhood chimney sweep.




Flat pane




Prismatic pane



L-shaped pane, left



L-shaped pane, right



U-shaped pane

39



For every fireplace the appropriate door.



Installation examples

The fireplace doors are adapted individually to your fireplace.

Different versions and designs are available on request.









"Spending the weekend in front of the fireplace is what I like best."

Our innovations to make the perfect flame

We have the highest requirements for the latest fireplace insert technology. We therefore rely on our own innovations for even higher efficiency and optimal energy usage for your fireplace.

High-quality materials, the best craftsmanship, the highest level of functionality and the longest service life, that is Spartherm quality that you can rely on.

4	2

Technology	43
Technical details	44
Sizes / the LINEAR mode of operation	45
Custom-made fireplace cassettes	46
Fireclay	47
Technical data	48-49





From an open to the perfect fire

The LINEAR Standard fireplace cassettes are matched perfectly to your fireplace with regard to their function, have a modern appearance and are easy and uncomplicated to install.

The benefits for you

High technical quality combined with a well-balanced design.
With Spartherm LINEAR Standard fireplace cassettes, you can now enjoy your fireplace with even more warmth and greater safety.

- Low-key frame solution, big viewing panel for optimum fire experience
- High efficiency
- Retrofitting a blower is possible
- Safe locking mechanism



Handle opened



Handle closed



Printed pane



Speed regulator for the hot-air blower

44

45



Your perfect fire


The production of your new fireplace cassette is carried out in accordance with the structural conditions and the exact dimensions that are determined on site by the fireplace installer.

Spartherm fireplace cassettes and doors are always manufactured precisely. As a result, every item produced is an individual piece.

Spartherm fireplace cassettes and doors are available in a wide range of fronts, shapes and versions. Furthermore, we also manufacturer fireplace cassettes and doors exactly in accordance with your expectations and wishes in our factory.

Incredible technology

The working principle of the custom-made fireplace cassettes



- 1 Firebox bottom, with moulded fire-clay bricks
- 2 Firebox walls lines with vermiculite
- 3 Double-layered base and walls to circulate the convection air
- **4** Air intake slats for the convection air (cold air)
- 5 Air outlet slats for the convection air (hot air)
- 6 Ash pan
- 7 Ash grate
- 8 Wood catcher
- **9** Heat exchanger pipes for the convection air

- **10** Integrated primary air control (handle adjustable/rotatable)
- 11 Primary air intake into the firebox
- **12** Secondary air intake (pre-heated air)
- 13 Control lever for continuous adjustment of the secondary air (operation using the ,cold hand')
- **14** Adjustable feet for aligning the cassettes
- 15 Optional fan

46

47








Principle of operation of Standard fireplace cassettes

- 1 Combustion air (in this case via optional flow pipe)
- 2 Cold air inlet
- 3 Warm air inlet
- 4 Secondary combustion air
- 5 Primary combustion air
- **6** Flue gas
- **7** Optional fan



Technical data

LINEAR Standard cassettes

				V	V								
				LINEAR	XS 500	LINEA	R S 600	LINEAF	M 700	LINEAF	R L 800	LINEAR	R XL 900
				D4	E4	D5	E5	D6	E7	D8	E10	D11	E14
		Fuel		Woo	d logs	Woo	d logs	Wood	d logs	Wood	logs	Wood	d logs
	Installati	on dimension height	mm	3.	45	5	10	6	10	7	10	8:	10
SI	Installat	ion dimension width	mm	4.	56	4	53	503		523		543	
Dimensions	Overall widt	h (frame: Standard) ¹⁾	mm	4	70	6	66	766		866		966	
Dim		Overall depth	mm	3	52	4	62	494		524		554	
	Flue pipe $arnothing$		mm	130		150		150		180		200	
	Energy efficiency class			A+	A+	A+	A+	A+	A+	A+	A+	Α	Α
		Nominal heat output	kW	4.0	4.6	4.9	4.9	5.9	6.9	7.9	9.9	10.5	14.0
		favourable	m³	-	-	-	-	-	-	-	-	-	-
	Heating condition ²⁾ sufficient for	less favourable	m³	-	-	-	-	-	-	-	-	-	-
	Summerention	unfavourable	m³	-	-	-	-	-	-	-	-	-	-
nce	T	hermal output range	kW	4.0-5.2	4.5-6.0	4.5-6.4	4.5-6.4	4.5-7.7	4.8-9.0	5.5-10.3	6.9-12.9	7.4-13.7	9.8-18.2
Operating performance		Wood feed quantity	kg/h	1.2	1.4	1.5	1.5	1.7	2.0	2.3	3.0	3.2	4.3
) perf	Efficiency		%	>	80	>	80	>	80	>	80	> 79	> 78
rating		Mass flow of flue gas	g/s	3.8	3.8	4.5	4.5	5.0	5.0	6.5	9.0	10.0	12.0
0pe	Flue gas tempe	erature at connection	°C	252	252	335	335	355	370	360	340	330	365
	Min. supply pressure at connection		Pa	1	12	1	12	1	2	1	2	1	12
	CO emission mg/		mg/m³	< 1250		< 1250		< 1250		< 1250		< 1250	
	Particle emissions		mg/m³	<	40	< 40		<	40	<	40	<	40
	Level 2 BlmSchV [Ordinance in the Implementation of the Federal Emission Control Act)			,	/	,	✓	,		•		,	/
	15a BVG (Austria)			,	/	,	✓	,		•	/	,	/
		EN 13240		,	/	,	✓	,	/	•	/	,	/
		DIN Plus		,	/	,	✓	,	/	,	/	,	/
		gensburg Regulation		,	/		✓	•		•	/	,	/
	Air Purity Direct	(for Switzerland)			/		✓	,	/	٧	/	,	
		Defra					✓		-		-		-
Info		Door function			ged		iged	hin		hin			ged
=		Weight	kg	5	54	8	33	10	03	13	30	1!	50

¹⁾Frame: Standard LINEAR cassettes → LINEAR XS 500 = 45mm / LINEAR S-XL = 60mm | Additional diaphragm widths are available | Subject to technical modifications.

²⁾ The values are intended merely for orientation. Targeted determination of the heating load must take place in accordance with TR-OL or be carried out in accordance with DIN EN 12831. The room heating capacity can also be varied appropriately by changing the amount of wood filled from 30% with regards to the nominal heat output.

Tec

Heating capacity

The heating capacity is dependent on the quantity and type of the fuel.

Room heating capacity

The nominal heat output depends on the heating conditions and the room size.

Heating condition	6 kW sufficient for	8 kW sufficient for
favourable	165 m ³	> 186 m ³
less favourable	95 m ³	145 m ³
unfavourable	65 m ³	98 m³

Source: Handbook of Heating and Air Conditioning Technology Recknagel/Sprenger

Custom-made heating cassettes

Value triple for calculating the chimney, in accordance with DIN 4705
Part 1 and Part 2 or EN 13384 at a nominal heat output in accordance with Section
7, Part 1




Heating	cassettes	small


Heating cassettes large


Wood logs	Lignite	Wood logs	Lignite			
custom	-made	custom-made				
custom	-made	custom-made				
of up t	to 700	from 700				
custom	-made	custom	ı-made			
custom	-made	custom	ı-made			
A+	A+	A+	A+			
6	.0	8.	.0			
16	55	> 1	186			
9	5	14	15			
6	5	9	8			
4.5 -	- 7.8	5.6 -	10.4			
1.7	1.3	2.4	1.8			
>	80	80				
4.7	5.6	7.2	8.0			
269	272	268	271			
1	2	12				
< 1	250	< 1250				
<	40	< 40				
٧	/	✓				
٧	/	✓				
٧	/	✓				
v	/	✓				
v	/	✓				
٧	/	٧	/			
v	/	٧	/			
hin	ged	hin	ged			
-			-			

LINEAR cassettes XS 500 / S 600 / M 700 / L 800 / XL 900

(This drawing is only an example. Please use the values from the table on the left-hand side)







Ac	cessories, optional *			
1	Flue gas offset bend			
2	Rear combustion air connection			
3	Blower with digital governor			
4	Governor housing			
5	Bottom combustion air connection			
6	Convection nozzle			
* only for the fireplace cassettes S 600 / M 700 / L 800 / XL 900				

Presentation of installation dimension:

The installation dimensions is the outer dimension of the visible fi replace insert area when installed.











Quality and advice from the specialist

As the market leader in the fireplace inserts and fireplace cassettes sectors, we focus on more than impressive technology and outstanding design. We also look to provide the highest levels of advice, expertise and perfect craftsmanship when we choose our partners. This commitment and a keen eye for detail transform your Spartherm chimney insert into an exclusive fireplace.

Our partners would be pleased to support you at every stage, from consultation to planning through to final assembly.

More information about fireplace cassettes can be found at www.spartherm.com/en/



Your specialist dealer		

Spartherm Feuerungstechnik GmbH

Maschweg 38 · 49324 Melle · Germany info@spartherm.com · www.spartherm.com



- $\begin{tabular}{ll} \hline \textbf{\mathfrak{f} www.facebook.com/sparthermfeuerungstechnik} & \hline \textcircled{\scriptsize @www.instagram.com/sparthermfeuerungstechnik} \\ \hline \end{tabular}$
- www.youtube.com/sparthermgermany